


SCALE	1:250	CREATION DATE	2025/09/19	DWG. NO. 03 OF 21
DRAWN BY	E.J.SWEENEY	DESIGN BY	E.J.SWEENEY	
CHECKED BY	E.C.HRYNYK	APPROVED BY	I.A.MCKINNON	
PLOT DATE	October 24, 2025			
				REV. 0



NOTE: MILL AND INLAY EXTENTS TO BE DISCUSSED AND CONFIRMED PRIOR TO CONSTRUCTION

PLAN
SCALE: 1:250

DETAILED CONSTRUCTION NOTES:


- ① REMOVE OR RELOCATE EXISTING SIGN.
- ② ADJUST CASTING TO FINISHED GRADE.
- ③ PRIOR TO INSTALLATION OF NEW INSPECTION CHAMBER AND CIPP RESTORATION, CONTRACTOR SHALL CONFIRM THE LOCATION AND CONDITION OF EXISTING SANITARY SERVICES USING CCTV INSPECTION.

CIVIL LEGEND

- CONCRETE INSTALLATION
REFER TO DRAWING FOR DETAILS
- MILL AND INLAY - REMOVE 50mm AND PLACE 50mm - LIMITS TO BE CONFIRMED IN THE FIELD PRIOR TO CONSTRUCTION
- FUTURE DEVELOPMENT SITE. FUTURE AAA INFRASTRUCTURE TO BE INSTALLED AS A PART OF DEVELOPMENT FRONTAGE.
- EXISTING ROAD HATCH SHOWN FOR PAVEMENT MARKING CLARITY. NOT INDICATIVE OF PAVING SCOPE.
- FULL DEPTH RESTORATION - 100mm OF ASPHALT (TWO LIFTS) ON TOP OF 100mm OF GRANULAR BASE AND 250mm OF GRANULAR SUB BASE
- 50mm THICK ASPHALT DRIVEWAY CONNECTION/ BIKE LANE
- OLDCASTLE SLAB 400mm X 400mm PAVERS, GRAY
- 150mm THICK CONCRETE DRIVEWAY CROSSING
- APPROXIMATE LOCATION OF UNDERGROUND SANITARY SPOT REPAIR. TO BE CONFIRMED WITH CCTV PRIOR TO CONSTRUCTION
- 150mm THICK TOP SOIL AND SEED
- FLEXIBLE BOLLARD
REFER TO NOTES FOR PRODUCT INFO
- PRECAST CONCRETE BARRIER CURB. SHY LINE TO BE AT AN OFFSET OF 150mm UNLESS STATED OTHERWISE

CIVIL NOTES

- 610mm AND FLEXIBLE BOLLARD:
 - MANUFACTURER: PEXCO LLC
 - MODEL: CITY POST - SURFACE MOUNT
 - COLOUR: WHITE
 - REFLECTIVE WHITE BANDS
 - CONTRACTOR SUPPLIED
- R7301 STAINLESS STEEL BOLLARD
 - MANUFACTURER: RELIANCE FOUNDRY
 - TOWNSHIP SUPPLIED
- REFER TO CIVIL DETAIL SHEET 15 FOR CURB RETURN PROFILES
- REFER TO LEGEND SHEET 02 FOR PAVEMENT MARKING AND SYMBOL DIMENSIONS
- CONTRACTOR TO CONFIRM CONDITION OF EXISTING CATCH BASIN LEADS AND SANITARY SERVICES WITH PUSH CAMERA AND/OR CCTV INSPECTION PRIOR TO CONNECTION
- PAVEMENT MARKINGS TO BE ERADICATED FROM STA 11+010 TO STA 11+550 AND STA. 12+000 TO STA. 12+420:
 - LIMITS OF ERADICATION ARE TO BE CONFIRMED IN THE FIELD WITH THE CONTRACT ADMINISTRATOR A MINIMUM OF 5 DAYS PRIOR TO ERADICATION WORK.



KEY PLAN



REV NO.	REVISION DESCRIPTION	DATE	DRAWN	APPR'D
0	60% DESIGN CIRCULATION	2025/10/24	EJS	IAM
1				
2				
3				
4				




ROAD
WORKS

ROADWORKS
STA 11+130 TO STA 11+280



1051 Vancouver St, Victoria, BC V8V 3K3
T: (250) 361-1320 F: (604) 629-5756

SCALE	1:250	CREATION DATE	2025/09/19	DWG. NO.	33995
DRAWN BY	E.J.SWEENEY	DESIGN BY	E.J.SWEENEY	04 OF 21	
CHECKED BY	E.C.HRYNYK	APPROVED BY	I.A.MCKINNON	REV.	0
PLOT DATE	October 24, 2025				



NOTE: MILL AND INLAY EXTENTS TO BE DISCUSSED AND CONFIRMED PRIOR TO CONSTRUCTION

PLAN
SCALE: 1:250


- DETAILED CONSTRUCTION NOTES:**
- ① REMOVE OR RELOCATE EXISTING SIGN.
 - ② ADJUST CASTING TO FINISHED GRADE.
 - ③ PRIOR TO INSTALLATION OF NEW INSPECTION CHAMBER AND CIPP RESTORATION, CONTRACTOR SHALL CONFIRM THE LOCATION AND CONDITION OF EXISTING SANITARY SERVICES USING CCTV INSPECTION.

CIVIL LEGEND

- CONCRETE INSTALLATION
REFER TO DRAWING FOR DETAILS
- MILL AND INLAY - REMOVE 50mm AND PLACE 50mm - LIMITS TO BE CONFIRMED IN THE FIELD PRIOR TO CONSTRUCTION
- FUTURE DEVELOPMENT SITE, FUTURE AAA INFRASTRUCTURE TO BE INSTALLED AS A PART OF DEVELOPMENT FRONTAGE.
- EXISTING ROAD HATCH SHOWN FOR PAVEMENT MARKING CLARITY. NOT INDICATIVE OF PAVING SCOPE.
- FULL DEPTH RESTORATION - 100mm OF ASPHALT (TWO LIFTS) ON TOP OF 100mm OF GRANULAR BASE AND 250mm OF GRANULAR SUB BASE
- 50mm THICK ASPHALT DRIVEWAY CONNECTION/ BIKE LANE
- OLDCASTLE SLAB 400mm X 400mm PAVERS, GRAY
- 150mm THICK CONCRETE DRIVEWAY CROSSING
- APPROXIMATE LOCATION OF UNDERGROUND SANITARY SPOT REPAIR. TO BE CONFIRMED WITH CCTV PRIOR TO CONSTRUCTION
- 150mm THICK TOP SOIL AND SEED
- FLEXIBLE BOLLARD
REFER TO NOTES FOR PRODUCT INFO
- PRECAST CONCRETE BARRIER CURB. SHY LINE TO BE AT AN OFFSET OF 150mm UNLESS STATED OTHERWISE


CIVIL NOTES

- 610mm AND FLEXIBLE BOLLARD:
 - MANUFACTURER: PEXCO LLC
 - MODEL: CITY POST - SURFACE MOUNT
 - COLOUR: WHITE
 - REFLECTIVE WHITE BANDS
 - CONTRACTOR SUPPLIED
- R7301 STAINLESS STEEL BOLLARD
 - MANUFACTURER: RELIANCE FOUNDRY
 - TOWNSHIP SUPPLIED
- REFER TO CIVIL DETAIL SHEET 15 FOR CURB RETURN PROFILES
- REFER TO LEGEND SHEET 02 FOR PAVEMENT MARKING AND SYMBOL DIMENSIONS
- CONTRACTOR TO CONFIRM CONDITION OF EXISTING CATCH BASIN LEADS AND SANITARY SERVICES WITH PUSH CAMERA AND/OR CCTV INSPECTION PRIOR TO CONNECTION
- PAVEMENT MARKINGS TO BE ERADICATED FROM STA 11+010 TO STA 11+550 AND STA. 12+000 TO STA. 12+420:
 - LIMITS OF ERADICATION ARE TO BE CONFIRMED IN THE FIELD WITH THE CONTRACT ADMINISTRATOR A MINIMUM OF 5 DAYS PRIOR TO ERADICATION WORK.



KEY PLAN





NOTE: MILL AND INLAY EXTENTS TO BE DISCUSSED AND CONFIRMED PRIOR TO CONSTRUCTION

PLAN
SCALE: 1:250

DETAILED CONSTRUCTION NOTES:


- ① REMOVE OR RELOCATE EXISTING SIGN.
- ② ADJUST CASTING TO FINISHED GRADE.
- ③ PRIOR TO INSTALLATION OF NEW INSPECTION CHAMBER AND CIPP RESTORATION, CONTRACTOR SHALL CONFIRM THE LOCATION AND CONDITION OF EXISTING SANITARY SERVICES USING CCTV INSPECTION.

CIVIL LEGEND

- CONCRETE INSTALLATION
REFER TO DRAWING FOR DETAILS
- MILL AND INLAY - REMOVE 50mm AND PLACE 50mm - LIMITS TO BE CONFIRMED IN THE FIELD PRIOR TO CONSTRUCTION
- FUTURE DEVELOPMENT SITE. FUTURE AAA INFRASTRUCTURE TO BE INSTALLED AS A PART OF DEVELOPMENT FRONTAGE.
- EXISTING ROAD HATCH SHOWN FOR PAVEMENT MARKING CLARITY. NOT INDICATIVE OF PAVING SCOPE.
- FULL DEPTH RESTORATION - 100mm OF ASPHALT (TWO LIFTS) ON TOP OF 100mm OF GRANULAR BASE AND 250mm OF GRANULAR SUB BASE
- 50mm THICK ASPHALT DRIVEWAY CONNECTION/ BIKE LANE
- OLDCASTLE SLAB 400mm X 400mm PAVERS, GRAY
- 150mm THICK CONCRETE DRIVEWAY CROSSING
- APPROXIMATE LOCATION OF UNDERGROUND SANITARY SPOT REPAIR. TO BE CONFIRMED WITH CCTV PRIOR TO CONSTRUCTION
- 150mm THICK TOP SOIL AND SEED
- FLEXIBLE BOLLARD
REFER TO NOTES FOR PRODUCT INFO
- PRECAST CONCRETE BARRIER CURB. SHY LINE TO BE AT AN OFFSET OF 150mm UNLESS STATED OTHERWISE

CIVIL NOTES

- 610mm AND FLEXIBLE BOLLARD:
 - MANUFACTURER: PEXCO LLC
 - MODEL: CITY POST - SURFACE MOUNT
 - COLOUR: WHITE
 - REFLECTIVE WHITE BANDS
 - CONTRACTOR SUPPLIED
- R7301 STAINLESS STEEL BOLLARD
 - MANUFACTURER: RELIANCE FOUNDRY
 - TOWNSHIP SUPPLIED
- REFER TO CIVIL DETAIL SHEET 15 FOR CURB RETURN PROFILES
- REFER TO LEGEND SHEET 02 FOR PAVEMENT MARKING AND SYMBOL DIMENSIONS
- CONTRACTOR TO CONFIRM CONDITION OF EXISTING CATCH BASIN LEADS AND SANITARY SERVICES WITH PUSH CAMERA AND/OR CCTV INSPECTION PRIOR TO CONNECTION
- PAVEMENT MARKINGS TO BE ERADICATED FROM STA 11+010 TO STA 11+550 AND STA. 12+000 TO STA. 12+420:
 - LIMITS OF ERADICATION ARE TO BE CONFIRMED IN THE FIELD WITH THE CONTRACT ADMINISTRATOR A MINIMUM OF 5 DAYS PRIOR TO ERADICATION WORK.



KEY PLAN



60% DESIGN CIRCULATION

DESIGN NO.

33995

REV NO.	REVISION DESCRIPTION	DATE	DRAWN	APPR'D
0	60% DESIGN CIRCULATION	2025/10/24	EJS	IAM
1				
2				
3				
4				



ROAD
WORKS


ROADWORKS
STA 11+420 TO STA 11+560



1051 Vancouver St, Victoria, BC V8V 3K3
T: (250) 361-1320 F: (250) 361-5758

SCALE	1:250	CREATION DATE	2025/09/19	DWG. NO.	06
DRAWN BY	E.J.SWEENEY	DESIGN BY	E.J.SWEENEY	OF	21
CHECKED BY	E.C.HRYNRYK	APPROVED BY	I.A.MCKINNON	REV.	0
PLOT DATE	October 24, 2025				

File: C:\ADS\ACCDocs\33995\Project Files\30_Drafting\202_Production\Phase2\33995_SH_ROADWORK_P12A.dwg



NOTE: MILL AND INLAY EXTENTS TO BE DISCUSSED AND CONFIRMED PRIOR TO CONSTRUCTION

PLAN
SCALE: 1:250

DETAILED CONSTRUCTION NOTES:


- ① REMOVE OR RELOCATE EXISTING SIGN.
- ② ADJUST CASTING TO FINISHED GRADE.
- ③ PRIOR TO INSTALLATION OF NEW INSPECTION CHAMBER AND CIPP RESTORATION, CONTRACTOR SHALL CONFIRM THE LOCATION AND CONDITION OF EXISTING SANITARY SERVICES USING CCTV INSPECTION.

CIVIL LEGEND

- CONCRETE INSTALLATION
REFER TO DRAWING FOR DETAILS
- MILL AND INLAY - REMOVE 50mm AND PLACE 50mm - LIMITS TO BE CONFIRMED IN THE FIELD PRIOR TO CONSTRUCTION
- FUTURE DEVELOPMENT SITE. FUTURE AAA INFRASTRUCTURE TO BE INSTALLED AS A PART OF DEVELOPMENT FRONTAGE.
- EXISTING ROAD HATCH SHOWN FOR PAVEMENT MARKING CLARITY. NOT INDICATIVE OF PAVING SCOPE.
- FULL DEPTH RESTORATION - 100mm OF ASPHALT (TWO LIFTS) ON TOP OF 100mm OF GRANULAR BASE AND 250mm OF GRANULAR SUB BASE
- 50mm THICK ASPHALT DRIVEWAY CONNECTION/ BIKE LANE
- OLDCASTLE SLAB 400mm X 400mm PAVERS, GRAY
- 150mm THICK CONCRETE DRIVEWAY CROSSING
- APPROXIMATE LOCATION OF UNDERGROUND SANITARY SPOT REPAIR. TO BE CONFIRMED WITH CCTV PRIOR TO CONSTRUCTION
- 150mm THICK TOP SOIL AND SEED
- FLEXIBLE BOLLARD
REFER TO NOTES FOR PRODUCT INFO
- PRECAST CONCRETE BARRIER CURB. SHY LINE TO BE AT AN OFFSET OF 150mm UNLESS STATED OTHERWISE

CIVIL NOTES

- 610mm AND FLEXIBLE BOLLARD:
 - MANUFACTURER: PEXCO LLC
 - MODEL: CITY POST - SURFACE MOUNT
 - COLOUR: WHITE
 - REFLECTIVE WHITE BANDS
 - CONTRACTOR SUPPLIED
- R7301 STAINLESS STEEL BOLLARD
 - MANUFACTURER: RELIANCE FOUNDRY
 - TOWNSHIP SUPPLIED
- REFER TO CIVIL DETAIL SHEET 15 FOR CURB RETURN PROFILES
- REFER TO LEGEND SHEET 02 FOR PAVEMENT MARKING AND SYMBOL DIMENSIONS
- CONTRACTOR TO CONFIRM CONDITION OF EXISTING CATCH BASIN LEADS AND SANITARY SERVICES WITH PUSH CAMERA AND/OR CCTV INSPECTION PRIOR TO CONNECTION
- PAVEMENT MARKINGS TO BE ERADICATED FROM STA 11+010 TO STA 11+550 AND STA. 12+000 TO STA. 12+420:
 - LIMITS OF ERADICATION ARE TO BE CONFIRMED IN THE FIELD WITH THE CONTRACT ADMINISTRATOR A MINIMUM OF 5 DAYS PRIOR TO ERADICATION WORK.



KEY PLAN



60% DESIGN CIRCULATION

DESIGN NO.

33995

REV NO.	REVISION DESCRIPTION	DATE	DRAWN	APPR'D
0	60% DESIGN CIRCULATION	2025/10/24	EJS	IAM
1				
2				
3				
4				




ROAD
WORKS

ROADWORKS
STA 12+000 TO STA 12+140




1051 Vancouver St, Victoria, BC V8V 3K3
T: (250) 361-1320 F: (604) 629-5756

SCALE	1:250	CREATION DATE	2025/09/19	DWG. NO.	07 OF 21
DRAWN BY	E.J.SWEENEY	DESIGN BY	E.J.SWEENEY		
CHECKED BY	E.C.HRYNYK	APPROVED BY	I.A.MCKINNON		
PLOT DATE	October 24, 2025				REV. 0



SCALE	1:250	CREATION DATE	2025/09/19	DWG. NO. 08 OF 21
DRAWN BY	E.J.SWEENEY	DESIGN BY	E.J.SWEENEY	
CHECKED BY	E.C.HRYNYK	APPROVED BY	I.A.MCKINNON	
PLOT DATE	October 24, 2025			
				REV. 0



NOTE: MILL AND INLAY EXTENTS TO BE DISCUSSED AND CONFIRMED PRIOR TO CONSTRUCTION

PLAN
SCALE: 1:250

DETAILED CONSTRUCTION NOTES:

- ① REMOVE OR RELOCATE EXISTING SIGN.
- ② ADJUST CASTING TO FINISHED GRADE.
- ③ PRIOR TO INSTALLATION OF NEW INSPECTION CHAMBER AND CIPP RESTORATION, CONTRACTOR SHALL CONFIRM THE LOCATION AND CONDITION OF EXISTING SANITARY SERVICES USING CCTV INSPECTION.


CIVIL LEGEND

- CONCRETE INSTALLATION
REFER TO DRAWING FOR DETAILS
- MILL AND INLAY - REMOVE 50mm AND PLACE 50mm - LIMITS TO BE CONFIRMED IN THE FIELD PRIOR TO CONSTRUCTION
- FUTURE DEVELOPMENT SITE. FUTURE AAA INFRASTRUCTURE TO BE INSTALLED AS A PART OF DEVELOPMENT FRONTAGE.
- EXISTING ROAD HATCH SHOWN FOR PAVEMENT MARKING CLARITY. NOT INDICATIVE OF PAVING SCOPE.
- FULL DEPTH RESTORATION - 100mm OF ASPHALT (TWO LIFTS) ON TOP OF 100mm OF GRANULAR BASE AND 250mm OF GRANULAR SUB BASE
- 50mm THICK ASPHALT DRIVEWAY CONNECTION/ BIKE LANE
- OLDCASTLE SLAB 400mm X 400mm PAVERS, GRAY
- 150mm THICK CONCRETE DRIVEWAY CROSSING
- APPROXIMATE LOCATION OF UNDERGROUND SANITARY SPOT REPAIR. TO BE CONFIRMED WITH CCTV PRIOR TO CONSTRUCTION
- 150mm THICK TOP SOIL AND SEED
- FLEXIBLE BOLLARD
REFER TO NOTES FOR PRODUCT INFO
- PRECAST CONCRETE BARRIER CURB. SHY LINE TO BE AT AN OFFSET OF 150mm UNLESS STATED OTHERWISE

CIVIL NOTES

- 610mm AND FLEXIBLE BOLLARD:
 - MANUFACTURER: PEXCO LLC
 - MODEL: CITY POST - SURFACE MOUNT
 - COLOUR: WHITE
 - REFLECTIVE WHITE BANDS
 - CONTRACTOR SUPPLIED
- R7301 STAINLESS STEEL BOLLARD
 - MANUFACTURER: RELIANCE FOUNDRY
 - TOWNSHIP SUPPLIED
- REFER TO CIVIL DETAIL SHEET 15 FOR CURB RETURN PROFILES
- REFER TO LEGEND SHEET 02 FOR PAVEMENT MARKING AND SYMBOL DIMENSIONS
- CONTRACTOR TO CONFIRM CONDITION OF EXISTING CATCH BASIN LEADS AND SANITARY SERVICES WITH PUSH CAMERA AND/OR CCTV INSPECTION PRIOR TO CONNECTION
- PAVEMENT MARKINGS TO BE ERADICATED FROM STA 11+010 TO STA 11+550 AND STA. 12+000 TO STA. 12+420:
 - LIMITS OF ERADICATION ARE TO BE CONFIRMED IN THE FIELD WITH THE CONTRACT ADMINISTRATOR A MINIMUM OF 5 DAYS PRIOR TO ERADICATION WORK.

KEY PLAN



60% DESIGN CIRCULATION

DESIGN NO.

33995

REV NO.	REVISION DESCRIPTION	DATE	DRAWN	APPR'D
0	60% DESIGN CIRCULATION	2025/10/24	EJS	IAM
1				
2				
3				
4				



ROAD
WORKS

ROADWORKS
STA 12+280 TO STA 12+420



1051 Vancouver St, Victoria, BC V8V 3K3
T: (250) 363-1320 F: (250) 363-5758

SCALE	1:250	CREATION DATE	2025/09/19	DWG. NO.	09
DRAWN BY	E.J.SWEENEY	DESIGN BY	E.J.SWEENEY	OF	21
CHECKED BY	E.C.HRYNRYK	APPROVED BY	I.A.MCKINNON	REV.	0
PLOT DATE	October 24, 2025				