

Official Community Plan

DPA No. 1: Natural Environment

Area

Land within the municipal boundaries of the Corporation of the Township of Esquimalt.

Designation

Development Permit Area No. 1 is designated for the purpose of establishing objectives for: Section 488 (1) (a)- protection of the natural environment, its ecosystems and biological diversity Note: For DPA justification and exemptions, please refer to the Official Community Plan, pages 75-77.).

If you are proposing a development within this DPA, please provide your application details in Section A. In Section B, please comment on how you propose to meet the DPA guidelines.


Section A

Application No.	Project Address	Applicant Name
DP		En Joseph State St

Section B


No.	Guideline	Comments (Please complete with NA where not applicable)
18.5.1	Lands Free of Development	у при
1	Land within 7.5m of the high watermark of the Gorge Waterway shall be retained in as natural a state as possible. Where the land has been previously altered, the area shall be restored with native trees and plants	NA
2	New buildings/ structures shall not be located within 20 m of the high watermark of the Gorge Waterway.	N/A
3	New buildings/ structures shall not be located within 10 m the high watermark of the Strait of Juan de Fuca.	N/A





4	Replacement of, expansion of, densification and intensification of the use of existing buildings within 20 m of the high watermark of the Gorge Waterway is discouraged; detached accessory dwelling units are strongly discouraged in this location.	N/A
5	Replacement of, expansion of, densification and intensification of the use of existing buildings within 10 m of the high watermark of the Strait of Juan de Fuca is discouraged and detached accessory dwelling units are strongly discouraged in this location.	NA
6	Variances to 'Building Height' and 'Siting Requirements' will be considered where natural areas and trees are being protected.	N/A
7	Consider the use of conservation covenants for areas having high ecosystem conservation values. Property owners are encouraged to work with local land trusts to protect natural features and valuable habitat areas through land covenants.	PROJUGO THROUGH BOULEJAD FLANTING APPLICATION
	· · · · · · · · · · · · · · · · · · ·	
18.5.2	Natural Features	
18.5.2	Natural Features Retain existing healthy native trees, vegetation, rock outcrops and soil wherever possible.	SOILS, TO BE REVAINED
	Retain existing healthy native trees, vegetation,	SOILS TO BE REVAINED
1	Retain existing healthy native trees, vegetation, rock outcrops and soil wherever possible. Preserve and enhance native tree and shrub clusters that overhang the waters edge as these provide shade, protection and feeding habitat for	SOILS, TO BE REVAINED N/A N/A






5	Design new development and landscaping to frame rather than block public views.	LANDSCAPING "LAYERED" FROM BOUNEJARD TO BUILDING ENTRY
6	Avoid disturbing, compacting and removing areas of natural soil as this can lead to invasion by unwanted plant species, poor water absorption and poor establishment of new plantings. Use of local natural soil in disturbed and restored areas will support re-establishment of ecosystem functions.	TO BE CONSIDERED AT TIME OF CONSTRUCTION.
18.5.3	Biodiversity	
1	New landscaping shall consist predominantly of native plant and tree species. Plants that are native to the Coastal Douglas-fir biogeoclimatic zone are preferred in landscape treatments as they provide habitat for threatened indigenous flora and fauna. Drought tolerant plants native to western North America, that are known to be non-invasive, are a good alternative choice for landscaped areas.	FINAL LANDSCAPING TO BE DETERMINED AT TIME OF CONSTRUCTION. "SUGUESTED PLANTING LIST" ACCOUNTS FOR NATIVE PLANTS.
2	In residential locations plan for 'nature out front'; for new landscaping in front and exterior side yards use a variety of site-appropriate, native species; thereby contributing positively to pedestrian friendly urban streets, future greenways and habitat enhanced corridors.	BOULEVARD PLANTING ASSOCIATION WITH THIS PROJUECT
3	Choose trees and plants for site conditions; consider shade, sunlight, heat, wind-exposure, sea spray tolerance, and year round moisture requirements in their placement.	TO BE DETERMINED BY LANDSCAPER
4	Consider the habitat and food needs of birds, pollinators, and humans in tree and plant species selection and placement; native plantings and food gardens compliment each other.	TO BE DETERMINED BY LANDSCAPER
5	Encourage native plant and food gardens to spill from private land into boulevards.	NOT PROJUDED ON THIS PROSECT








6	Avoid monoculture plantings, especially expanses of turf grass outside of playing field sites.	MIXTURE OF GRASS AREAS AND PLANTING
		BEDS PROVIDED IN DESIGN
7	Snags, logs, driftwood and rock cairns may be used as interesting landscaping features that also provide habitat for native flora and fauna.	TO BE DETERMINED BY LANDSCAPER
8	Avoid using fast-growing non-native plants to cover and retain soils as they may become invasive and a constraint to the establishment of other plants.	NOT CONSIDERED (NON NATIVE PLANTS)
9	Locate civil servicing pipes/lines under driveways or other paved areas to minimize tree root damage. (Note that the majority of trees have their roots in the top 0.6 m of the soil).	WILL BE CONSIDERIED/PROVIDED AT LONSTRUCTION
10	Design retaining wall spacing and landscape planting areas of sufficient width and depth to support plantings (eg. provide larger spaces for trees).	PLANTING AREAS ALLOW FOR THIS
11	Support the daylighting of portions of the stormwater system for enhanced habitat.	NOT CONSIDERRED
12	Aim to meet the Canadian Landscape Standards in all landscaping installations.	LANDSRAPING TO BETO BUSCA STANDARDS
18.5.4	Natural Environment	
1	Strategically locate leafy trees/ hedges and water features to mask urban noises such as traffic, garbage collection and delivery locations. Consider that leafy rough barked trees, vine covered walls and natural ground cover materials (mulch, soil) will help dampen urban noise.	HEDWES AND LEAFY TREES PROPOSED
2	Use International Dark-Sky Association approved lighting fixtures in outdoor locations. Outdoor lighting shall be no brighter than necessary, be fully shielded (directed downward and designed to serve pedestrian needs), have minimal blue light emissions and only be on when needed. Avoid vanity lighting, and lighting directed into the night sky and trees tops.	LIGHTING TO BE DEGIGNED AT TIME OF CONGTRUCTION.








3	Light spillage on to waterways is strongly discouraged.	N/A
4	Place trees and vegetation near sources of air pollution including busy roadways, to assist in reduction of air pollution through the collection of particulate matter on leaves and needles, and absorption of toxic gases, including but not limited to: ozone, nitrogen dioxide, sulfur dioxide, carbon monoxide, carbon dioxide, cadmium, chromium, nickel and lead.	TREES PLACED NEAR ROADS
18.5.5	Drainage and Erosion	
1	Preserve, restore and enhance treed areas. Trees are the most effective form of absorbent landscaping due to their extensive root zones and their ability to both absorb water from the soil and intercept precipitation on leaves, needles and branches. Consider that native conifers are well adapted to local wet winters.	REPLACEMENT TREES AND NIEW TREES PROPOSED
2	Reduce the impact of surges in stormwater on shorelines by designing on-site stormwater retention systems to contain the first 3 centimetres [1.25 inches] of precipitation on site, per precipitation event; and incorporating rainwater collection systems into roof design and landscaping.	No DESIGN PROJUZO.
3	Consider using shared private/ public rain gardens. Direct a portion of stormwater to adjacent public open spaces, when deemed appropriate by the Director of Engineering and Public Works.	NO RAIN GARDENS ADJACENT
4	Maximize the ratio of planted and pervious surfaces to unplanted surfaces, and design paved areas to direct water towards vegetated areas, to help reduce surface run off. Where paved surfaces are needed, intersperse with drought resistant vegetation and trees, to help absorb stormwater, provide shade and reduce the local heat island effect.	PLANTING FROUDED IN BOONEVARD AS PART OF DEVELOPMENT








5	Use porous surfaces to enhance stormwater infiltration, permeable paving is preferable for all open air parking areas. Ensure installation methods contribute to sustained permeability and retention of stormwater on the site.	W. PERMEABLE SURFACES PROVIDED
6	Choose absorbent landscaping materials; leaf mulches, wood chips and good quality top soil, over gravel, pavers and concrete. Provide mulch of organic, locally derived materials; leaf mulch from local tree leaves is most desirable.	AREAS PROJUZO
7	Incorporation of rain gardens, bio-swales, rain barrels, and even small depressions (puddles) into landscaping will help reduce surges of stormwater entering local waterways.	NONE PROJUCED
8	Planting densities should ensure that vegetated areas will have near 100% plant coverage after two full growing seasons.	PROJURD THROUGH "SUGGESTED PRANTING LIST". FINAL DESIGN AT CONSTRUCTION STACE
18.5.6	Protect, Restore and Enhance Shorelines	
1	Waterfront property owners are encouraged to become familiar with and adopt a 'soft shore' restoration approach to the care of their foreshore property (i.e. Green Shores for Homes).	N/A
2	Avoid the expansion of dock area, bulkheads, groins or other shoreline hardening structures. Removal or reductions in the surface area of existing private docks is encouraged.	W/A
3	Where shoring methods are required to prevent erosion or the sloughing of the shoreline, choose bio-engineering methods over the use of sea-walls or retaining walls. Where sea-walls or retaining walls are the only means of effectively preventing erosion, design in consultation with qualified environmental professionals, as well as engineering professionals.	N/A








18.5.7	Native Bird Biodiversity	
1	Protect and enhance habitat features like mature trees, shrub clusters, native fruit bearing shrubs, fresh water ponds and ephemeral damp areas (puddles).	REPLACEMENT TREES PROVIDED
2	Encourage increased front yard habitat along quieter streets to reduce bird vehicle conflicts and enhance the pedestrian experience through native plantings.	BOUNEVARD PLANTING + FRONT YARD PLANTING TO CONTRIBUTE TO THIS
3	Sustain a mix of habitat types; including forest, shrub-land, meadow, riparian wetland and coastal shoreline ecosystems in landscaping.	MIX OF PLANTING AREAS PROVIDED
4	Incorporate a vertical vegetation structure [vertical habitat] including layers of ground cover, shrub, understorey and canopy in landscape design.	CONSIDIENCED AS PER LANDSLAPE PLAN.
5	Choose a range of native plant species and sizes; a mix of coniferous and deciduous trees will enhance bird species diversity.	SULLIESTED PLANTING LIST" FROJERS A RANGE OF PLANT SPECIES
6	Incorporate architectural features that limit collisions between birds and windows including patterned, frosted or tinted glass, exterior louvers, blinds, sun shades and canopies.	BLINDS TO BE INSTALLED
7	Cap and screen all ventilation pipes and grates, avoid openings greater than 2.0 x 2.0 cm.	AS REQUIRED BY BUILDING CODE







Official Community Plan

DPA No. 3: Enhanced Design Control Residential

Area

All lands zoned for two-unit dwellings or zoned as Comprehensive Development Districts for residential developments only are designated as part of Development Permit Area No. 3- Enhanced Design Control- Residential as shown on "Development Permit Areas Map" (Schedule "H") of this Plan.

Designation

Development Permit Area No. 3 is designated for the purpose of establishing objectives for:

• Section 488 (1) (e)- establishment of objectives for the form and character of intensive residential development. .Note: For DPA justification and exemptions please refer to the Official Community Plan, page 84.

If you are proposing a development within this DPA, please provide your application details in Section A. In Section B, please comment on how you propose to meet the DPA guidelines.


Section A

Application No.	Project Address	Applicant Name
DP		Tours .

Section B


No.	Guideline	Comments (Please complete with NA where not applicable)
20.5		
1	The fronts of the buildings should be designed to create the appearance of smaller structures either by staggering the dwelling units or visually breaking up the façade with architectural detailing while still maintaining a complementary streetscape.	NA
2	Innovative and creative site-specific two-unit dwellings are encouraged where usable open space is maintained either on the ground (yard) or as rooftop gardens. Setbacks to the street may be reduced to maximize property use.	WA






3	Front to back duplexes are generally discouraged unless they can be designed to eliminate negative impacts to the immediate neighbours such as shading of gardens, overlook of outdoor amenity areas and violation of privacy.	NA
4	Side by side, up and down, or staggered unit configurations are preferred as these result in a greater number of units facing the street, less disruption of privacy, and a more equitable division of outdoor amenity areas between the two dwelling units.	NA
5	The use of exterior building materials similar to those used in older residential neighbourhoods (i.e. combinations of wood, brick, stucco, and stone) is encouraged.	N/A
6	Rooflines of new development should relate in height, shape and pitch to existing residential buildings in the immediate area. For corner sites, the building design should avoid having large unbroken sloped roof areas facing the street.	N/A
7	To create interest in the façade of the buildings facing the street, the incorporation of architectural elements such as bay windows, covered porches, verandas and prominent front doors is encouraged.	N/A
8	Buildings should be designed to minimize visual intrusion on to the privacy of surrounding homes. Some overlook of adjoining yards and neighbouring decks may be unavoidable; however, additional privacy should be achieved by insetting balconies, decks and patios into the building or by screening them with latticework or landscaping. Windows should be spaced so that they do not align directly with those of other buildings.	NIA
9	The height and massing of new two-unit dwellings should be designed to minimize the casting of shadows on to the private outdoor space of adjacent residential dwellings	NA





10	A landscaping plan showing ground cover areas, planting beds, shrubbery and trees (both existing and proposed) is required. Landscaping should add to the aesthetic appeal of the streetscape as well as provide privacy between dwelling units.	DONE SO THROSCH THE ADDITION OF BOOLEVARD PLANTING
11	The provision of private open space should be part of an overall site development and landscape plan and should take into consideration general site circulation patterns (including parking), existing landscape features, sun access, privacy and usability.	PRIVATE SPACE PROJETO IN REAR YARD AND SUNKIEN PATHO
12	Retention and protection of trees and the natural habitat is encouraged where possible.	NOT POSSIBLE, NEW TREES ADDED
13	Parking areas, garages and driveways should appear as a minor component of the site when viewed from the street. The building of curving access roads and driveways helps to avoid views from the street of large expanses of paving. The use of shared driveways is encouraged.	SHARRD TURN AROUND PROJURD. BOULEVARD PLANTINGS TO DETRACT FROM PARKING AREA
14	The use of permeable and decorative surfacing materials, such as brick, concrete pavers, textured concrete, coloured paving or grasscrete is encouraged in place of solid expanses of asphalt or concrete.	NOT PROVIDED
15	Where possible, hydro meters should not be placed on the front façade of a building and, if placed in a manner which is visible from the street, will be appropriately screened by the owner in a manner consistent with BC Hydro requirements.	NOT DETERMINED AT THIS TIME.
16	Where an existing single-unit dwelling is being converted to a two-unit dwelling both the original structure and the addition shall be in complementary architectural style and constructed of complementary exterior finishes including roofing material, window treatments, exterior finishes, door styles and trims.	N/A






17	Roof styles and pitches of the original and new portions of the building must be complimentary.	W/A
18	For new or converted two unit dwellings, garages and parking areas are encouraged to be located in the rear yard. Shared driveways are preferred to access the rear yard.	N/A
19	Where two single lane driveways serve a two unit lot, landscaping features are encouraged between the driveways.	N/A

20.6	Guideline- Single-unit Infill Housing	
20.6.1	Relationship to Existing Houses Where an existing single-unit residence is to be retained and a second residence placed on the parcel, the existing dwelling is to be upgraded and made to be complementary with the new construction. The intent of this guideline is not to encourage the replication or imitation of surrounding	N/A
2	buildings but rather the design of structures that complement the streetscape. Where two or more new separate dwellings are situated on a parcel or within a comprehensive development zone, the buildings shall be designed as part of a comprehensive scheme with all buildings being finished in complementary materials and incorporating complimentary architectural details. The intent of this guideline is not to encourage the replication or imitation of surrounding buildings but rather the design of structures that complement the streetscape.	THIS HAS BEEN DONE THROUGH THE USR OF SIMINAR ARCHITECTURIE. AND FINISHING MATTERIALS.






Where new infill single houses are proposed, the design of the new houses should be complementary in scale, size, exterior finishes, rooflines, and colours to the predominant styles of housing in the neighbourhood. It is important to ensure that the new construction fits with the overall scale and character of existing houses. The intent of this guideline is not to encourage the replication or imitation of surrounding buildings but rather the design of structures that complement the streetscape.	HOUSES ARE COMPLEMENTARY IN SCALE AND SIZE. ADD VANUE TO THE STREET SCAPE.
--	--

20.6.2	Massing	
1	New structures should be designed so that the overall massing is in keeping with other single-unit residences in the immediate area. New structures for lots other than corner or double frontage lots should be limited to one and one half storeys.	MASSING MATCHES OTHER NEW SED'S IN ARRA.
2	New structures, which are two storeys in height, should be designed so that the second storey is partially concealed within the slope of the roof to minimize the height of the building. The use of dormers set into the roof is preferred to a flat roof or a peaked roof set over the second storey.	ARCHITECTURAL STYLE DORS NOT ALLOW

20.6.3	Privacy/Screening/Shadowing	
1	Proposed infill dwellings should have only a minimal impact on adjacent homes and be separated from neighbouring residences by vegetation, screening, natural elevation differences, or a combination of these features.	ROAD AND PROPERTY SLOPES WEST (HIGH) TO EAST (LOW) PROVIDING A NATURAL TIERING AFFECT ALONG THE STREESCAPE SCREENING PROJUED BRINESS PROPERTIES.
2	Windows, decks and patios should be located so as to minimize intrusion on to the privacy of adjacent properties.	SCREENING PROJOBED THROUGH FENCING AND DECKS ARE SET TO ONE SIDE OF THE HOUSE.






3	Infill dwellings should be sited to minimize the casting of shadows on to the private outdoor space of adjacent residential dwellings.	THIS IS NOT POSSIBLE ON SMALL LOT
		LONDITIONS
		·

20.6.4	Landscaping	
1	Proposals for single-unit infill housing must include a landscape plan showing hard landscaping (i.e., parking areas, fences, and patios) as well as lawns, trees, shrubs, planting areas and proposed plant species.	PROJUDED
2	Retention and protection of trees and the natural habitat is encouraged wherever possible.	REHABILITATE AS POSSIBLE

20.6.5	Private Open/Yard Space	
1	Any proposal for single-unit infill housing should provide for usable, private outdoor areas for each dwelling, at grade.	PATIOS PROJUED AND DECKS PROJUED







Official Community Plan

DPA No. 7 Energy Conservation & Greenhouse Gas Reduction

Area

Land within the municipal boundaries of the Corporation of the Township of Esquimalt

Designation

Development Permit Area No. 7 is designated for:

- Section 488 (1)(h)- Energy Conservation; and
- Section 488 (1)(j)- GHG emissions reduction. *Note: For DPA justification and exemptions please refer to the Official Community Plan, pages 95-96.*

If you are proposing a development within this DPA, please provide your application details in Section A. In Section B, please comment on how you propose to meet the DPA guidelines.


Section A

Application No.	Project Address	Applicant Name
DP	-	Jones Tours

Section B


No.	Guideline-	Comments
24.5.1	Siting of buildings and structures	
1	Orient buildings to take advantage of site specific climate conditions, in terms of solar access and wind flow; design massing and solar orientation for optimum passive performance.	SITE ORIENTATION AND SIZE DOES NOT ALLOW FOR THIS
2	Build new developments compactly, considering the solar penetration and passive performance provided for neighbouring sites, and avoid shading adjacent to usable outdoor open spaces.	THIS IS INFELL DEVELOPMENT, SHE ORIENTATION AND SIZE DOES NOT ALLOW FOR THIS
3	In commercial, residential or commercial mixed-use designated areas with taller developments, vary building heights to strategically reduce the shading on to adjacent buildings.	WA-






4	Provide space for pleasant pedestrian pathways between buildings.	PROVIDED BETWEEN PROPERTY LINE AND BULDING
5	Strategically site buildings to sustain and increase the community's urban forest tree canopy cover.	NEW TREE PLANTING PROPOSED
6	Provide space for significant landscaping including varying heights of trees, shrubs and ground covers.	PLAN.
7	Provide intuitive pedestrian access to storefronts and businesses with site connectivity to nearby amenities and services to help promote walking and the use of other active transportation modes.	N/A
8	Provide usable outdoor amenities such as seating, food gardens, mini-libraries, and play spaces in semi-public areas to enhance the experience of walking and recreating in the neighbourhood.	N/A
9	In residential neighbourhoods, provide space for larger trees and a second row of street trees as this will enhance the pedestrian experience by lowering wind velocity at street level, reducing excessive heating at ground level and absorbing vehicle and other urban noises.	CONSIDERED AS PART OF BOULEVARD ENHANSMENT FORMING PART OF OVERALL DEVELOPMENT





24.5.2	Form and exterior design of buildings and	d structures
1	Orient larger roof surfaces to the south for potential use of solar panels or photo-voltaic roofing.	PROJUNED
2	Use roof designs that reduce heat transfer into neighbouring buildings, helping reduce the local heat island effect and the need for cooling of buildings in warmer months.	THIS HAS NOT BEEN CONSIDERED
3	Place more windows on the south side of buildings to increase solar gain, and fewer/ smaller windows on the north side to minimize heat loss.	THIS IS NOT POSSIBLE DUE TO SITE SIZE AND DELENTATION.
4	Use roof over-hangs, fixed-fins or other solar shading devices on south and west facing windows to reduce peak summer heat gain while enabling sunlight penetration in winter months.	THIS HAS NOT BEEN CONSIDERIED
5	Install adjustable overhangs above windows that can help control the amount of sun exposure in warmer months thereby reducing need for cooling.	NOT CONSIDERED
6	Provide building occupants with control of ventilation; i.e. windows that open.	OPERABLE WINDOWS PROJUCED
7	Skylights are discouraged as they decrease insulating values and can interfere with solar panel installation.	No SKYHAHTS PROJIDED IN DESIGN
8	Add rooftop patios and gardens, particularly food producing gardens, as they can contribute to local resilience, livability, and reduction in greenhouse gas production by reducing food transportation costs.	NOT PERMITTED OR PROLIDED
9	Install greenhouses for growing food on rooftops where neighbourhood privacy and light intrusion concerns are mitigated.	NOT CONSIDIERED
10	Avoid heavily tinted windows or reflective glass which will diminish the natural daylighting of interior spaces, thereby requiring increased energy requirements for interior lighting.	WINDOWS TO BE DESIGNED TO BENEFIT THE HOUSE THERMALLY






11	In exposed marine locations select durable materials that will withstand weather and sea spray, to ensure low maintenance costs and infrequent replacement needs.	NA		
----	---	----	--	--

24.5.3	Landscaping	
1	Develop a front yard landscape design that is natural and delightful so residents do not need to leave the neighbourhood to experience nature.	DONE BEYOND REQUIREMENTS BY DEVELOPING BONLEVARD
2	Choose open space and landscaping over dedicating space to the parking and maneuvering of private motor vehicles.	FARKING 15 A BYLAW REQUIRIEMENT
3	Conserve native trees, shrubs and soils, thereby saving the cost of importing materials and preserving already sequestered carbon dioxide.	SOILS TO BE CONSERVED
4	Use deciduous trees for landscaping along southern exposures, as they provide shade in the summer and allow more sunlight through in the winter.	FINAL LANDS PLANTING TO BE DONE AT TIME OF CONSTRUCTION. DECIDOOS TREES PROPOSED IN SOUTHERN BOULEVARD
5	Strategically place taller trees and vegetation on the south and west sides of buildings where there is more direct sun exposure.	PROPERTY ORIGINATION AND SIZE DOES NOT ALLOW FOR THIS
6	Strategically place coniferous trees such that they can buffer winter winds.	THIS HAY NOT BEEN CONSIDERED DUE TO SITECRIENTATION AND SIZE
7	As context and space allow, plant trees that will attain a greater mature size, for greater carbon storage; removal of healthy trees is discouraged as the loss of the ecosystem services provided by larger trees will take many years to recover.	PROPOSED TREE LOCATION WILL ALLOW FOR
8	Plant trees with a larger canopy cover along roadways and sidewalks, thereby providing shading of paved areas, lowering the heating of paved surfaces and reducing the wind velocities in these pedestrian areas.	NOT POSSIBLE ON THIS PROPERTY DUE TO REQUIRED TORN AROUND. BOULDUARD PLANTING WILL BE PROVIDED TO PRODUCE THIS AFFECT






9	Plant shorter and sturdier vegetation closer to buildings and other structures, and taller vegetation further away to avoid potential damage from strong winds blowing vegetation against buildings.	FINAL PLANTING TO BE DETERMINIZED AT CONSTRUCTION. "SUGGESTED PLANTING LIST" ON DWG'S ALLOWS FOR THIS
10	For commercial areas, strategically increase green space between buildings, allowing room for landscaped pathways to improve the pedestrian experience, promote walking, and provide for improved light penetration on to sidewalks.	N/A
11	For parking areas and along boulevard/ sidewalk edges; plant trees to provide shade, store carbon and reduce the heat island effect.	PLANTING PROJINED IN BOUNEVARD

24.5.4	Machinery, equipment and systems exter	nal to buildings and other structures
1	For external lighting: • Choose efficient low-energy and long life technologies;	LIGHTING DESIGN TO BE CONFRETED FROM TO AT TIME OF CONSTRUCTION.
1	 Design lighting to reinforce and compliment existing street lighting; 	
:	 Use motion-sensitive or solar-powered lights whenever possible; 	
	 Layer lighting for varying outdoor needs; and 	
	Provide lighting systems that are easily controlled by building occupants.	,
2	Use heat pumps, solar panels, green (living) roofing or an innovative system to improve a building's energy performance.	TO BE CONSIDERED AT TIME OF CONSTRUCTION
3	Use durable, vandalism and graffiti resistant materials where neighbourhood surveillance may be limited.	DURABLE MATERIALS PROPOSED (HARDE-
4	Design for on-site heat recovery and re-use of water.	TO BEZ CONSIDERED AT TIME OF CONSTRUCTION
		CONSTRUCTION






5	In commercial and industrial areas: design bicycle parking facilities to be inviting for cyclists. Locate bike racks near the main building entrance, with adequate lighting and weather protection.	W/A
6	In commercial areas, provide fast charge electric vehicle charging stations near locations that have quick customer turnover, and ensure the station is easily accessible, well lit, and visible from the public street.	N/A
7	Provide car sharing facilities that are well lit, available for residents, and easily accessed from the public street.	N/A

24.5.5	Special Features	
1	Select building materials that have been shown to have a high level of durability for the use intended.	HARIE PANEL IS HIGHLY DURABLE
2	Use wood for construction as a means to sequester carbon dioxide - North American grown and sustainably harvested wood is preferable for building construction.	WOOD FRAMING TO BE USED
3	Select local and regionally manufactured building products whenever possible to reduce transportation energy costs.	TO BE LONGIDERIED AT TIME OF CONSTRUCTION
4	Reuse of existing buildings and building materials is encouraged.	NOT CONSIDERED FOR THIS PROSECT
5	Choose materials that have a high likelihood of reuse or recycling at end of life.	NOT CONSIDERED FOR THIS PROSECT.







Official Community Plan

DPA No. 8 Water Conservation

Area

Land within the municipal boundaries of the Corporation of the Township of Esquimalt

Designation

Development Permit Area No. 8 is designated for:

• Section 488 (1)(i)- Water conservation. Note: For DPA justification and exemptions please refer to the Official Community Plan, pages 100-101.

If you are proposing a development within this DPA, please provide your application details in Section A. In Section B, please comment on how you propose to meet the DPA guidelines.


Section A

Application No.	Project Address	Applicant Name
DP		f nin onto

Section B

No.	Guideline-	Comments
25.5.1	Building and Landscape Design Reduce the burden on built stormwater	
	infrastructure by designing on-site retention systems to retain the first three centimetres (1.25") of stormwater on site, per precipitation event.	No MANALEMENT PLAN DEVELOPED
2	Provide space for absorbent landscaping, including significantly sized trees on the site and by not	- SORY LANDSCAPING PROVIDED.
	allowing underground parking structures to extend	- LARGER TREES INDICATED ON PROPERTY
	beyond building walls.	AND ADJACENT BOOLEVARD
3	Incorporate rainwater collection systems into roof design; consider using living roofs and walls as part of a rainwater collection system.	No COLLECTION SYSTEM PROJIDED
4	Incorporate rain gardens into landscaping and direct	
4	rainwater towards vegetated areas.	No RAIN GARDENS PROVIDED






DPA No. 8 Water Conservation

5	Intersperse paved surfaces with drought resistant vegetation that will provide shade on those surfaces and design the paved surfaces to drain into the vegetation.	SMALL LOT DOES NOT ALLOW FOR MUCH INTERSPERSED PAVED SURFACES. PATHWAYS TO FRONT ENTRY ARE AWAY FROM BUILDING FORE TO ALLOW FOR PLATING NO CONSIDERATION TO SHADING ALTHOUGH WILL OCCUR
6	Design landscaping with more planted and pervious surfaces than solid surfaces.	PARKINA AFRAS MINIMIZED AS MURIT AS POSSIBLE
7	Direct stormwater towards adjacent public spaces, with rain gardens/ bioswales located on public property where it would benefit both the new development and the municipality and where it is deemed appropriate by municipal staff.	NA

25.5.2	Landscaping- Select Plantings for Site an	d Local Conditions
1	Retain existing native trees vegetation, and soil on site.	DOWE WHERE POPEBLE (LEAR YARD)
2	Plant species native to the Coastal Douglas-fir biogeoclimatic zone, as they are most suited to our climate and require little additional irrigation once established.	EXACT PLANTING NOT DONE AT THIS TIME. "SULLEGSED PLANTING LIST" TAKES THIS INTO ACCOUNT.
3	Consider shade, sunlight, heat, wind-exposure and sea spray, as well as water needs in the selection and placement of plant species.	SEE # 2
4	Group plants with similar water needs into hydrozones.	SEE WZ






DPA No. 8 Water Conservation

25.5.3	Landscaping- Retaining Stormwater on	Site (absorbent landscaping)
1	Preserve and restore treed areas. Trees are the most effective form of absorbent landscaping due to their extensive root zones and their ability to both absorb water from the soil and intercept precipitation on leaves, needles and branches. Consider that native conifers are well adapted to local wet winters.	TREES ARE PROPOSED ON LANDSCAPING PRAN
2	Use pervious landscaping materials to enhance stormwater infiltration; permeable paving is preferable for surface parking areas.	NOT PROPIDED
3	Avoid disturbing, compacting and removing areas of natural soil, as these are naturally absorbent areas.	DONE WHERE POHIBLE (REAR YARD)
4	Locate civil servicing lines along driveways and other paved areas, to lessen the disturbance of natural soils and loss of their natural absorption qualities.	TO BE CONSIDERED AT TIME OF CONSTRUCTION.
5	Use good quality top soil and compost for the finish grading of disturbed areas to contribute to the water holding capacity of newly landscaped areas.	WILL BE PRONOED
6	Choose bark mulches or woodchips for walking paths for enhanced absorption.	Not PROLIDED.
7	Plant at densities that will ensure vegetated areas have 100% plant canopy coverage after two full growing seasons. Consider that understory native plants are adapted to local climates, absorb seasonal soil moisture and reduce compaction due to foot traffic.	EXACT PLANTING NOT DONE AT THIS TIME.





DPA No. 8 Water Conservation

25.5.4	Landscaping- Water Features and Irrigati	ion Systems
1	Use automated high efficiency irrigation systems where irrigation is required.	No IRRIGATION PROLIDED
2	Incorporate stormwater retention features into irrigation system design.	No IRRIGATION PROLOED
3	Use recirculated water systems for water features	
3	such as pools and fountains.	NO WATTER FEATORES
4	Install plantings and irrigation systems to the Canadian Landscape Standard.	PROPOSED AS INDICATED